



Morricite Rust and Oil Inhibitor Primer

DESCRIPTION

Morricite Rust and Oil Inhibitor Primer is a very low viscosity, 100% solids, two-component, epoxy coating, exclusively used for poorly prepared surfaces over petroleum-based, oil-contaminated concrete for garage or auto shop floor with long pot life and good blush resistance. It provides good adhesion to concrete and rusty metal.

Morricite Primer 151 deeply penetrates the surface to mitigate the oil and its odor and bond to the oil contaminants embedded in the concrete.

ADVANTAGES

- Easy to apply
- Oil block primer for concrete
- Deep substrate penetration results in complete adhesion
- Encapsulates and adheres to rusty metal embedded inside the concrete floor

USES

- Garage Floor
- Service Floor
- Auto Shop Floor

TYPICAL PHYSICAL PROPERTIES

Mix Ratio: A: B 2:1 by volume

Color: Clear amber

Solid Content: 100%

Pot Life: > 2 hours

Shelf Life: 2 years (stored @ maximum temperature of 85°F)

APPLICATION

- The surface must be prepared by shot blasting, grinding and degreasing.
- Morricite #151 is an oil tolerant primer that can be placed at roughly 80 ft²/gal or less if the surface is highly irregular.
- Morricite primer 151 mixed material is flood coated into the floor and scrubbed into the pores with a stiff-bristle brush. The scrubbing action accomplishes two functions. First, it forces the material into the pores and secondly, the residual oil contaminate, which is lifted from the pores, is thoroughly mixed with the Morricite primer 151 system.
- Sand is broadcast into the primed surface and allowed to cure prior to placement of the epoxy flooring system.
- Prior to placement of the flooring system, the excess sand is removed and surface must be checked for excessive oil contamination, which would be evident by touch.

SAFETY

For industrial and professional use ONLY.

For detailed safety guidelines, please refer to the Safety Data Sheet (SDS)

WARRANTY INFORMATION

Values stated herein are typical values based on periodic testing and product experience. MTT DISCLAIMS ALL OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING WITHOUT LIMITATION THOSE OF MERCHANTABILITY OR FITNESS FOR PARTICULAR PURPOSE. Where customer demonstrates non-conformance of product to typical values stated herein, MTT will supply replacement product or, at its discretion, credit customer's account for the purchase price of non-conforming product. Recommendations herein as to the surface preparation, application, maintenance, and other matters involving storage, handling, or use of product are based on the best information available. Because MTT has no control over such matters, or over substrate or other conditions that may affect ultimate performance, customer has the obligation to determine suitability of product for the intended purpose. MTT SHALL HAVE NO RESPONSIBILITY FOR ANY CONSEQUENTIAL, INCIDENTAL, SPECIAL, EXEMPLARY OR PUNITIVE DAMAGES BUT ONLY FOR THE REPLACEMENT OR CREDIT MENTIONED ABOVE. All claims for replacement or credit must be made within one year from date of shipment. The sale and purchase of product from MTT are subject in each case to MTT's terms and conditions of purchase.

Master Terrazzo Technologies / PO Box 226 / Bristol, PA 19007
8000 Bristol Pike / Levittown, PA 19057 / www.masterterrazzo.com
215.949.1474 / Fax 215.949.9422 / Email:office@masterterrazzo.com