



## PRODUCT DATA SEALON 132

### Waterbased Sealer Sealon WB

**Morricite SealOn WB Sealer 132** is a ready-to-use, water based, emulsion type, clear acrylic surface sealer, which does not alter the natural appearance of concrete, tile, masonry, etc. It can be applied at temperatures as low as 55 °F to dry surface.

#### ADVANTAGES

- One component
- Fast drying, early protection
- Non-toxic, non-flammable
- Not affected by sunlight, mild acids, alkalis', aliphatic solvents, oil, grease
- Resists oil laden dust pickup, industrial exhaust, atmospheric soot
- Excellent resistance to impact and abrasion
- Does not support mold, fungi, bacteria, staph
- Scrubbable after 12 hours

#### USES

For Sealing and waterproofing of concrete, epoxy or terrazzo, masonry, stucco, stone, and other construction materials.

#### TYPICAL PHYSICAL PROPERTIES

|                 |                     |                             |                     |
|-----------------|---------------------|-----------------------------|---------------------|
| Mix ratio:      | One component       | Weight per Gallon:          | Approx. 7.6 lbs/gal |
| Color:          | Clear (after cured) | Volatile Organic Compounds: | 57 – 60 g/l         |
| Solids Content: | 18 – 22 %           | Slip Resistance:0.6 minimum | ASTM: D-2047        |

#### APPLICATION

- Surface to be sealed shall be structurally sound, clean and free of oil, grease, wax and loose matter.
- Surface must be dry or may be damp but have no standing water. Brush out excess water. For proper drying apply above 55 °F minimum or higher.
- Apply with brush, roller, or spray. Two coats are recommended for optimum results. Apply second coat as soon as first coat appears dry (15 to 60 minutes).
- Clean tools and equipment in clean water promptly after use.
- Store in warm area. KEEP FROM FREEZING.

#### SAFETY

For industrial and professional use **ONLY**.

For detailed safety guidelines, please refer to the product Safety Data Sheet (SDS)

#### WARRANTY INFORMATION

Values stated herein are typical values based on periodic testing and product experience. MTT DISCLAIMS ALL OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING WITHOUT LIMITATION THOSE OF MERCHANTABILITY OR FITNESS FOR PARTICULAR PURPOSE. Where customer demonstrates non-conformance of product to typical values stated herein, MTT will, supply replacement product or, at its discretion, credit customer's account for the purchase price of non-conforming product. Recommendations herein as to the surface preparation, application, maintenance, and other matters involving storage, handling, or use of product are based on the best information available. Because MTT has no control over such matters, or over substrate or other conditions that may affect ultimate performance, customer has the obligation to determine suitability of product for the intended purpose. MTT SHALL HAVE NO RESPONSIBILITY FOR ANY CONSEQUENTIAL, INCIDENTAL, SPECIAL, EXEMPLARY OR PUNITIVE DAMAGES BUT ONLY FOR THE REPLACEMENT OR CREDIT MENTIONED ABOVE. All claims for replacement or credit must be made within one year from date of shipment. The sale and purchase of product from MTT are subject in each case to MTT's terms and conditions of purchase.

Master Terrazzo Technologies / PO Box 226 / Bristol, PA 19007

8000 Bristol Pike / Levittown, PA 19057 / www.masterterrazzo.com 215.949.1474 / Fax 215.949.9422 / Email:office@masterterrazzo.com